

Supporting Information

Electrochemical Deposition of Pt Nanoparticles on Carbon Nanotube Patterns for Glucose Detection

Zhiyuan Zeng,^[a] Xiaozhu Zhou,^[a] Xiao Huang,^[a] Zhijuan Wang,^[a] Yanli Yang,^[a,b] Qichun Zhang,^[a] Freddy Boey,^[a,b] Hua Zhang^{[a,b],*}

^aSchool of Materials Science and Engineering, Nanyang Technological University, 50 Nanyang Avenue, Singapore 639798, Singapore

^bCentre for Biomimetic Sensor Science, Nanyang Technological University, 50 Nanyang Drive, Singapore 637553.

Tel: (+65) 6790 5175; Fax: (+65) 6790 9081.

E-mail: HZhang@ntu.edu.sg; h Zhang166@yahoo.com.

Website: <http://www.ntu.edu.sg/home/hzhang/>.




Figure S1. Performance of SWCNT pattern electrode in amperometric detection of H₂O₂ at +0.55 V vs Ag/AgCl (sat. KCl) at 25 °C.




Figure S2. Amperometric response of GOx/BSA/SWCNT electrode upon successive additions of glucose solution in a 10 mM phosphate buffer (pH 7.4, containing 3 mM *p*-benzoquinone as the redox mediator) at + 0.35 V vs Ag/AgCl (sat. KCl) at 25 °C.