Supporting Information for

Antibacterial Au nanostructured surfaces

Songmei Wu,^{1,2*} Flavia Zuber³, Juergen Brugger²,

Katharina Maniura-Weber³, and Qun Ren^{3*}

¹ School of Science, Beijing Jiaotong University,

No.3 Shangyuancun, Haidian District, Beijing 100044, P. R. China

² Microsystems Laboratory, École Polytechnique Fédérale de Lausanne,

Station 17, 1015 Lausanne, Switzerland

³Laboratory for Biointerfaces, Empa, Swiss Federal Laboratories for Materials Science and Technology, Lerchenfeldstrasse 5, 9014 St. Gallen, Switzerland 1. Plasma etching of W through alumina nanoporous template



Figure S1 : Top view of alumina nanoporous template after plasma etching of W. The nanopores are self-organized in a near-hexagonal pattern as indicated. Based on which nanorings and nanonuggets are formed.



Figure S2 : Cross section image of the template after plasma etching of W-30s



Figure S3 : Cross section image of the template after plasma etching of W-60s. The W layer is thick (1 μ m) in this case.

- 10 μm Mmg = 30.00 K X H WD = 3.4 mm Stage at T = 28.6 ° File Name = 3060 μf EPFL-CMI
- 2. Comparison of antibacterial properties for nanopillar structures

Figure S4 : Au nano-dots on W reference substrate by deposition time of 30 s. Most of the S. *aureus* cells appear alive.



Figure S5 : Au nano-pillar on W reference substrate by deposition time of 120 s. Nearly all the S. *aureus* cells appear dead.