


## Electronic Supplementary Information

### Fabrication of flexible polymer-GaN core-shell nanofibers by the combination of electrospinning and hollow cathode plasma-assisted atomic layer deposition

Cagla Ozgit-Akgun,<sup>\*ab</sup> Fatma Kayaci,<sup>ab</sup> Sesha Vempati,<sup>a</sup> Ali Haider,<sup>ab</sup> Asli Celebioglu,<sup>ab</sup> Eda Goldenberg,<sup>a</sup> Seda Kizir,<sup>ab</sup> Tamer Uyar<sup>ab</sup> and Necmi Biyikli<sup>\*ab</sup>

**Table S1.** Tensile test results of pristine nylon 6,6 and nylon-GaN core-shell nanofiber mats.

Sample	Nylon 6,6 nanofiber mat	Nylon 6,6-GaN core-shell nanofiber mat
<b>Young Modulus</b>	265.33±26.46 MPa	16.11±1.59 MPa
<b>Ultimate Stress (Tensile Strength)</b>	23.08±6.73 MPa	1.83±0.17 MPa
<b>Elongation at Break</b>	21.63±5.77%	0.61±0.12%



**Figure S1.** DMA results: (a) stress vs. strain plot of nylon-GaN core-shell nanofiber mat, and (b) storage modulus vs. temperature plots of pristine nylon 6,6 and nylon-GaN core-shell nanofiber mats.