

Sodium-Deficient O3- $\text{Na}_{0.9}\text{Mn}_{0.4}\text{Fe}_{0.5}\text{Ti}_{0.1}\text{O}_2$ as a cathode material for sodium-ion batteries

Xiaolei Jiang,^{a*} Fangdong Hu,^a Junshu Zhang^b

a School of Chemistry and Chemical Engineering, Linyi University, Linyi, 276005, P.R. China

b School of Chemistry and Chemical Engineering, Shandong University, Jinan 250100, P. R. China

**Corresponding author:*

Xiaolei Jiang

E-mail:jiangxiaolei@lyu.edu.cn




Fig. S1 (A) XRD pattern of NMFO and (B) the initial three galvanostatic charge and discharge curves of the NMFO cycled between 2 and 4 V at a rate of 0.1 C.




Fig. S2 (A) The initial three galvanostatic charge and discharge curves of the NMFTO cycled between 1.5 and 4.2 V at a rate of 0.1 C; (B) the cycling performance at a rate of 0.1 C.




Fig. S3 (A) The initial three galvanostatic charge and discharge curves of the NMFTO cycled between 2 and 4.2 V at a rate of 0.1 C; (B) the cycling performance at a rate of 0.1 C.




Fig. S4 The CV curves of NMFTO for the first three cycles between (A) 2.0-4.0 V, (B) 1.5-4.2 V and (C) 2-4.2V.

Table S1 EIS parameters and diffusion coefficient of sodium ion for NMFTO.

Cycles	R_s (Ω)	R_{ct} (Ω)	σ ($\Omega\text{cm}^2\text{s}^{-0.5}$)	D (cm^2s^{-1})	Error (%)
5th	5.0	162	24.4	6.1E-13	1.95