

Electronic Supplementary Information (ESI) for

Electrospun Three-Layered Polymer Nanofiber-Based Porous Carbon Nanotubes for High-Capacity Energy Storage

Jun Seop Lee,^{a,b,II} Jaemoon Jun,^{a,II} Sunghun Cho,^c Wooyoung Kim^a, and Jyongsik Jang^{a*}

^a *School of Chemical and Biological Engineering, College of Engineering, Seoul National University (SNU), 599 Gwanangno, Gwanak-gu, Seoul, 151-742 (Korea). Fax: +82-2-888-7295; Tel: 82-2-880-8348; e-mail: jsjang@plaza.snu.ac.kr*

^b *Materials Science and Engineering Program and Texas Materials Institute, The University of Texas at Austin, Austin, TX 78712, (USA)*

^c *School of Chemical Engineering, Yeungnam University, 280 Daehak-Ro, Gyeongsan 38541, Korea*

^{II} These authors contributed equally to this work.

1. Apparatus of dual-nozzle co-electrospinning.




Figure S1. Real-photo image of dual-nozzle co-electrospinning apparatus.

2. CV curves of other PCNTs.




Figure S2. CV curves of (a) PCNT_1, (b) PCNT_2, and (c) PCNT_3 with different voltage scan rates ($10 - 100 \text{ mV s}^{-1}$).

3. Galvanostatic charge/discharge curves of other PCNTs.




Figure S3. Gavanostatic charge/discharge curves of (a) PCNT_1, (b) PCNT_2, and (c) PCNT_3 with different current densities (0.5 – 10 A g⁻¹).