Supporting information for

Low-Voltage-Driven and Highly-Diffractive Holographic Polymer Dispersed Liquid Crystals with Spherical Morphology

Haiyan Peng,^a Lei Yu,^a Guannan Chen,^a Trent William Bohl,^a Yunsheng Ye,^a Xingping Zhou,^{a,b,*} Zhigang Xue,^a V. A. L. Roy,^c Xiaolin Xie^{a,d,*}

^a Key Laboratory for Material Chemistry of Energy Conversion and Storage, Ministry of Education, School of Chemistry and Chemical Engineering, Huazhong University of Science and Technology, Wuhan 430074, China.

^b Hubei Key Laboratory of Material Chemistry and Service Failure, School of Chemistry and Chemical Engineering, Huazhong University of Science and Technology, Wuhan 430074, China.

^c Department of Physics and Materials Science, City University of Hong Kong, Tat Chee Avenue, Kowloon Tong, Hong Kong SAR, China.

^d National Anticounterfeit Engineering Research Center, Wuhan 430074, China.

Corresponding authors: X. Zhou (xpzhou@mail.hust.edu.cn),

X. Xie (xlxie@mail.hust.edu.cn)



119.07 (a), 115.10 (h), 110.03 (b), 67.80 (j), 31.28 (k), 19.26 (l), 13.85 (m).



Figure S2. Mass spectrum of the as-synthesized 4OCB. Calculated [C17H18NO]⁺

(MH^+)): m/z 252.1344; found:	252.1378.
----------	-------------------------	-----------



Figure S3. Representing polarization dependent diffraction efficiency, η , for the HPDLC gratings (a) without 4OCB, and (b) with 5 wt% 4OCB.



Figure S4. TGA curves of the HPDLC gratings without and with 5 wt% 4OCB. No weight loss is noted up to 104 °C, and only 1 wt% weight loss occurred up to 180 °C.