

Supplementary Information for

Influence from the types of surface functional groups of RGO on the performances of thermal interface materials

Yunfei Sun^{a*}, Yanfeng He^b, Bo Tang^{b*}, Chongben Tao^a, Jianmin Ban^a, Li Jiang^a

^aCollege of Electronic and Information Engineering, Suzhou University of Sciences and
Technology, Suzhou, Jiangsu 215009, People's Republic of China

^bSchool of Petroleum Engineering, Changzhou University, Changzhou city 213016, China.

Corresponding authors: 113965203@qq.com; tangbo@cczu.edu.cn.




Fig. S1 Stress-strain curves of the pristine ER and resulting TIMs.

Table S1 Mechanical performances of various samples.

Samples	Properties	Ultimate strength (enhancement factor)	Stretch limits (strain %)
	Pristine ER		1
	RGO (h, e)-5 wt%	0.98	220
	RGO (x, e)-5 wt%	0.97	220
	RGO (h, h)-5 wt%	0.94	200
	RGO (x, h)-5 wt%	0.94	210
	RGO (h, e)-10 wt%	0.96	210
	RGO (x, e)-10 wt%	0.96	210
	RGO (h, h)-10 wt%	0.93	210
	RGO (x, h)-10 wt%	0.92	200