Gravity driven ultrafast removal of organic contaminants across catalytic superwetting membrane

Zhigao Zhu, Lingling Zhong, Zhiqiang Zhang, Huarui Li, Wenxin Shi, Fuyi Cui*, Wei Wang*

State Key Laboratory of Urban Water Resource and Environment (SKLUWRE), School of Environment, Harbin Institute of Technology, Harbin 150090, P. R. China.

Corresponding Author

Email: wangweirs@hit.edu.cn and cuifuyi@hit.edu.cn




Fig. S1 Average diameters of the as-prepared $MnCl_2/PAN$ and relevant carbonized nanofibrous membranes with various contents of $MnCl_2$ to PAN: (a) 10, (b) 30 and (c) 50 wt%.




Fig. S2 FE-SEM images of the as-prepared and carbonized nanofibrous membranes fabricated from various atom ratios of Mn and Co. (a, d) 1/1, (b, e) 1/2 and (c, f) 0/1.




Fig. S3 Time dependence for MeB degradation using $Mn_xCo_y@CNFs$ fabricated from various atom ratios of Mn and Co.




Fig. S4 Average diameters of relevant as-prepared and carbonized nanofibers.




Fig. S5. Photographs showing the MnO/Co@SiO₂-CNFMs containing various SiO₂ NPs.




Fig. S6 Different magnification TEM images of MnO/Co@SiO₂-CNFMs after 5 cycles filtration degradation.




Fig. S7 XPS spectrum of MnO/Co@SiO₂-CNFMs.




Fig. S8 High resolution N1s of MnO/Co@SiO₂-CNFMs.