Supporting Information for

Five-minute synthesis of silver nanowires and their roll-to-roll processing for large-area organic light emitting diodes

Hwansu Sim,^{‡a} Chanho Kim,^{‡b} Shingyu Bok,^a Min Ki Kim,^b Hwisu Oh,^a Guh-Hwan Lim,^a Sung Min Cho,^{*b} and Byungkwon Lim^{*a}

 ^a School of Advanced Materials Science and Engineering, Sungkyunkwan University (SKKU), Suwon 16419, South Korea. E-mail: blim@skku.edu
^b School of Chemical Engineering, Sungkyunkwan University (SKKU), Suwon 16419, South Korea. E-mail: sungmcho@skku.edu

[‡]These authors contributed equally to this work.



Fig. S1. SEM image of a single Ag NW longer than 100 μ m.



Fig. S2. Powder XRD pattern of the as-synthesized Ag NWs.



Fig. S3. SEM images of samples taken at different stages of the synthesis: (A) 2 min, (B, C) 3 min, and (D) 4 min.



Fig. S4. UV/vis spectra recorded at different stages of the synthesis that had been conducted with (A) EG:PG ratio of 3:1 and (B) EG only.



Fig. S5. SEM image of the product synthesized with PG in the absence of EG.



Fig. S6. Total absorption, reflection, and transmission spectra of the DD-stabilized Ag NW film recorded using a UV-vis spectrometer equipped with an integrating sphere.



Fig. S7. Plots of haze versus transmittance for transparent electrodes fabricated with bare Ag NWs, DD-stabilized Ag NWs, and commercial Ag NWs with different diameters.