

Electronic Supplementary Information

Enhanced water transport in AEMs based on poly (styrene-ethylene-butylene-styrene) triblock copolymer for high fuel cells performance

Xueqiang Gao ^{a,b}, Hongmei Yu ^{*a}, Bowen Qin ^{a,b}, Jia Jia ^{a,b}, Jinkai Hao ^{a,b}, Feng Xie ^{a,b}, Zhigang Shao ^{*a}.

Captions of ESI

Figure S1 The ¹H NMR and ¹³C NMR spectra of polymers. a SEBS; b CMSEBS; c QASEBS

Figure S2 The FT-IR spectrum of polymers. a. SEBS; b. CMSEBS; c. QASEBS

Figure S3 The TGA curves of SEBS、CMSEBS and QASEBS

Figure S4 Tyndall effect of AEI solution.

Figure S5 Polarization curves for AEMFCs with AEM-20 membrane for a study on various anode dew point: 50 °C (red circles), 65 °C (black square). Test conditions, cell temperature 60 °C, the cathode dew point 50 °C, back pressure 0.1 MPa.

Figure S6 the change of the elements content in AEM before (A) and after (B) durability test.




Figure S1 the ^1H NMR and ^{13}C NMR spectra of polymers. a SEBS; b CMSEBS; c QASEBS




Figure S2 The FT-IR spectrum of polymers. a. SEBS; b. CMSEBS; c. QASEBS




Figure. S3 The TGA curves of SEBS、CMSEBS and QASEBS



Figure S4 Tyndall effect of AEI solution.




Figure S5 Polarization curves for AEMFCs with AEM-20 membrane for a study on various anode dew point: 50 °C (red circles), 65 °C (black square). Test conditions, cell temperature 60 °C, the cathode dew point 50 °C, back pressure 0.1 MPa.




Figure S6 the change of the elements content in AEM before (A) and after (B) durability test.