

Supporting Information

Selenium Clusters in Zn-glutamate MOF Derived Nitrogen-Doped Hierarchically Radial-Structured Microporous Carbon for Advanced Rechargeable Na-Se Battery

Wenda Dong,^a Hao Chen,^a Fanjie Xia,^{a,b} Wenbei Yu,^a Jianping Song,^a Sijia Wu,^a Zhao Deng,^a Zhi-Yi Hu,^{a,b} Tawfique Hasan,^c Yu Li,^{a,b,*} Hongen Wang,^a Lihua Chen^a and Bao-Lian Su^{a,d,e,*}

^a State Key Laboratory of Advanced Technology for Materials Synthesis and Processing, Wuhan University of Technology, 122 Luoshi Road, 430070, Wuhan, Hubei, China. *E-mail: yu.li@whut.edu.cn and bao-lian.su@whut.edu.cn

^b Nanostructure Research Centre (NRC), Wuhan University of Technology, 122 Luoshi Road, 430070 Wuhan, Hubei, China.

^c Cambridge Graphene Centre, University of Cambridge, Cambridge CB3 0FA, United Kingdom.

^d Laboratory of Inorganic Materials Chemistry (CMI), University of Namur, 61 rue de Bruxelles, B-5000 Namur, Belgium. *E-mail: bao-lian.su@whut.edu.cn

^e Clare Hall, University of Cambridge, Herschel Road, Cambridge CB3 9AL, United Kingdom.




Figure S1. TGA curves of Se@N-HRMC.




Figure S2. Raman spectra of the commercial Se, N-HRMC, Se/N-HRMC and Se@N-HRMC.




Figure S3. XPS survey spectrum of Se@N-HRMC.




Figure S4. XPS spectra of the Se/N-HRMC composite. (a) survey spectrum, high resolution XPS spectra of (b) C 1s, (c) N 1s and (d) Se 3d.




Figure S5. CV curves of the Se/N-HRMC electrode at 1.0-3.0 V at a potential sweep rate of 0.1 mV s⁻¹.




Figure S6. The cycle performance of N-HRMC in 0.2C.




Figure S7. The SEM picture and photo of treated Se.




Figure S8. Nyquist plots of Se@N-HRMC and Se/N-HRMC electrodes collected after 2 cycles.

Insert: Solid lines in Nyquist plots are fitted to the equivalent circuit.




Figure S9. The beaker cell test of (a) Se@N-HRMC, and (b) Se/N-HRMC.