

Electronic Supplementary Material

A refined phase diagram of tert-butanol – water system and implications on lyophilization process optimization of pharmaceuticals

Bakul S. Bhatnagar^{a,e}, Jayesh Sonje^a, Evgenyi Y. Shalaev^{c,d}, Susan W. H. Martin^b, Dirk L. Teagarden^b, and Raj Suryanarayanan^a

^aDepartment of Pharmaceutics, College of Pharmacy, 308 Harvard St. SE,
University of Minnesota, Minneapolis, MN 55455, USA

^bPfizer Biotherapeutics, Pfizer Inc., St. Louis, MO, USA

^cPfizer Groton Laboratories, Eastern point Road, Pfizer Inc., Groton, CT 06340, USA

^dPharmaceutical development, Allergan Inc, Irvine, CA, USA.

^ePfizer Biotherapeutics, Pfizer Inc., Andover, MA, USA

Correspondence to: Raj Suryanarayanan, PhD

Telephone: (612) 624-9626 Fax: (612) 626-2125

Email: surya001@umn.edu

Data points for phase diagram:

The determination of zero heating rate relevant calculations are mentioned in *table S1*.

Table S1: Determination of zero heating rate

Data from experiments on unannealed solutions						
TBA, % w/w	Water, % w/w	Eutectic melting temp from unannealed systems - 2C/min	Eutectic melting temp from unannealed systems - extrapolated to 0°C/min	Equation from the unannealed data extrapolated to a zero-heating rate	Correction factor	Calculated eutectic melt for annealed solutions
2.5	97.5	-7.81 ± 0.06	-8.56 ± 0.04	y = 0.3742x - 8.5583	-0.75	-8.20
5	95	-7.61 ± 0.12	-8.36 ± 0.00	y = 0.3789x - 8.3552	-0.75	-7.9
10	90	-6.92±0.06	-8.20±0.03	y = 0.6724x - 8.2001	-1.28	-7.40
15	85	-6.40±0.25	-8.19±0.09	y = 0.9029x - 8.1921	-1.79	-7.81
20	80	-5.93±0.19	-8.17±0.01	y = 1.1537x - 8.1713	-2.24	-8.17
25	75	-5.89±0.07	-8.17±0.09	y = 1.1669x - 8.1712	-2.28	-8.17