

Supporting Information

White-light-emitting flexible display devices based on double network hydrogels crosslinked by YAG:Ce phosphors

Yawen Xu,^{ab} Jing Chen,^{*b} Hua Zhang,^b Hua Wei,^b Linjie Zhou,^b Zhenwu Wang,^b

Yuexiao Pan,^d Xinyan Su,^a Afang Zhang,^a Jun Fu^{*bc}

a. School of Materials Science and Engineering, Shanghai University, 99 Shangda Road, Shanghai 200444, China.

b. Ningbo Institute of Materials Technology & Engineering, Chinese Academy of Sciences, 1219 Zhongguan West Road, Ningbo 315201, China.

c. School of Materials Science and Engineering, Sun Yat-sen University, 135 Xingang Road West, Guangzhou 510275, China.

d. College of Chemistry and Materials Engineering, Wenzhou University, Wenzhou 325035, China.

Corresponding authors: J. Chen (jing.chen@nimte.ac.cn) or J. Fu (fujun8@mail.sysu.edu.cn)

Table S1. The CIE coordinates of coated LED by varying the current of blue LED lump.

	20 mA	18 mA	16 mA	14 mA	12 mA	10 mA	8 mA	6 mA	4 mA	2 mA
X	0.3303	0.3312	0.3312	0.3314	0.3300	0.3299	0.3298	0.3295	0.3288	0.3277
y	0.3217	0.3281	0.3296	0.3314	0.3307	0.3329	0.3356	0.3390	0.3338	0.3416