

Supplementary Information for

**Enhanced lithium storage performance of porous Si/C composite
anodes through using recrystallized NaCl template**

Ye Hong^a, Haiyong Dong^b, Jianhong Li^b, Qianqian Hu^{b,c,d}, Zilong Tang^e, Jian Ouyang^a, Xiaojun Wang^a,

Dan Xiang^{a*}

^a *Industrial Training Center, Guangdong Polytechnic Normal University, Guangzhou 510665, China*

^b *GAC Automotive Research & Development Center, Guangzhou 511434, China*

^c *Guangzhou Institute of Energy Conversion, Chinese Academy of Sciences; CAS Key Laboratory of Renewable Energy; Guangdong Provincial Key Laboratory of New and Renewable Energy Research and Development, Guangzhou 510640, China*

^d *University of Chinese Academy of Sciences, Beijing 100049, China*

^e *State Key Laboratory of New Ceramics and Fine Processing, School of Materials Science and Engineering, Tsinghua University, Beijing 100084, China*

*Corresponding author: Prof. Dan Xiang
E-mail: hongye@gpnu.edu.cn; gpnuxd@163.com;




Fig. S1 Particle size distribution curves of (a) NaCl templates and (b) Si/C composites.




Fig. S2 SEM images of (a) Si/C-N composite and (b) commercial nano-Si powders.




Fig. S3 (a) TEM, (b) HRTEM and (c) corresponding SAED patterns of Si/C-L composite.




Fig. S4 Rate performance of Si/C-N electrode from 0.2 A g⁻¹ to 5 A g⁻¹.




Fig. S5 Charge/discharge profiles of Si/C-L electrode at various rates.




Fig. S6 Nyquist plots and corresponding fitting curves of Si/C-L and Si/C-S electrodes.

Table S1 R_s , R_{int} and R_{ct} values of Si/C-L and Si/C-S electrodes.

Sample	R_s	R_{int}	R_{ct}
Si/C-L	3.09	9.51	22.86
Si/C-S	4.06	6.64	15.11