Electronic Supplementary Information

Novel Organic-Inorganic Hybrid powder SrGa₁₂O₁₉:Mn²⁺-Ethyl Cellulose for Efficiency Latent Fingerprint Recognition via Time-Gated Fluorescence

Jun'an Lai¹, Zhangwen Long¹, Jianbei Qiu^{1, 2*}, Dacheng Zhou^{1, 2}, Qi Wang^{1, 2*}, Yong Yang¹, Songhan Hu¹, Zhe Wang¹, Ke Zhang¹,

¹College of Materials Science and Engineering, Kunming University of Science and Technology, Kunming 650093, China

² Key Lab. of Advanced Materials of Yunnan Province, Kunming 650093, China

*Corresponding author: Jianbei Qiu, E-mail address: <u>qiu@kmust.edu.cn</u>

Qi Wang, E-mail address: 363270387@qq.com

Tel:+86-871-5188856; Fax: +86-875-5188856

Site	Wyckoff	х	У	Z	occupancy
	position				
Sr1	2d	0.3333	0.6667	0.75	1
Gal	2a	0	0	0	1
Ga2	4e	0	0	0.2574	1
Ga3	4f	0.3333	0.6667	0.02686	1
Ga4	4f	0.3333	0.6667	0.18992	1
Ga5	12k	0.169	0.33692	0.89085	1
O1	4e	0	0	0.14825	1
O2	4f	0.3333	0.6667	0.94681	1
O3	6h	0.1842	0.36729	0.25	1
O4	12k	0.1569	0.31287	0.05212	1

O5	12k	0.5055	0.00999	0.15081	1
----	-----	--------	---------	---------	---

Site	Wyckoff	Х	У	Z	occupancy
	position				
Sr1	2d	0.3333	0.6667	0.75	1
Gal	2a	0	0	0	1
Ga2	4e	0	0	0.25719	1
Ga3	4f	0.3333	0.6667	0.02692	1
Ga4	4f	0.3333	0.6667	0.18992	1
Ga5	12k	0.16896	0.33692	0.89084	1
O1	4e	0	0	0.14809	1
02	4f	0.3333	0.6667	0.94666	1
O3	6h	0.18415	0.36729	0.25	1
O4	12k	0.15692	0.31287	0.05211	1
O5	12k	0.50547	0.00999	0.15073	1

Table S2 The Wyckoff position, atomic coordinates and the occupancies of SGO: 2%Mn(B)

Table S3 The mass and atomic percent of each element in SGO: 5 % Mn by SEM-EDS analysis

Element	Weight %	Atomic %	Net Int.	Error %	Kratio	Z	R	А	F
O K	32.84	68.49	324.7	8.39	0.09	1.18	0.88	0.24	1.00
MnK	0.75	0.46	32.7	3.33	0.01	0.94	1.02	0.96	1.12
GaK	58.93	28.20	1190.1	1.10	0.54	0.90	1.05	1.01	1.01
SrK	7.47	2.85	25.2	4.90	0.06	0.84	1.06	0.97	1.00



Fig. S1 The SEM-EDS analysis of SGO: 5% Mn.



Fig. S2 (a) The TL spectra of SGO: xMn^{2+} (x = 0%, 0.5%,1%, 2%,3%,4%,5%); (b) The normalized TL spectra of SGO: 0.5%Mn²⁺ and un-doped SGO.

Fig. S3 The time-gated LFPs visualization by SGO: Mn-EC powder.

Table S4 The color purities of SGO: xMn2+ (x =0.5%, 1%, 2%, 3%, 4%, 5%)

1					, ,	
concentration	0.5%%	1%,	2%	3%	4%	5%
color purity	80.61%	84.75%	81.28%	80.69%	83.9%	81.6%

Fig. S4 FTIR spectra (a) (b) FTIR spectra of SGO: Mn and SGO: Mn combined with LFPs; (c) (d) FTIR spectra of EC and EC combined with LFPs.

Fig. S5 (a) Fingerprint recognition on smooth glass surface; (b)fingerprint recognition on rough wood surface.

Fig. S6 The visualization of LFPs from different donors. (a) 24 years old male; (b) 28 years old male; (c) 24 years old female; (d) 30 years old male; (e) 26 years old female; (f) 24 years old male.

Fig. S7 (a)The fingerprint recognition of cross-fingerprints, (b) The typical pores by partial magnification of the cross-fingerprints.

Fig. S8 Fingerprint recognition after heating at 100 °C for different time, (a)10 min; (b)30 min.

	5 days	10 days	30 days	RT	50 °C	100 °C	150 ℃	200 °C
UV on								
UV off								
UV on								
UV off								
UV on			\$			-		
UV off								

Fig. S9 Weather resistance of SGO: Mn-EC powder.