

Supporting information

Formation and manipulation of ferrofluid droplets with magnetic fields in a microdevice: A numerical parametric study

Venoos Amiri Roodan¹, Jenifer Gómez-Pastora², Ioannis H. Karampelas¹, Cristina González-Fernández³, Eugenio Bringas³, Inmaculada Ortiz³, Jeffrey J. Chalmers², Edward P. Furlani^{1,4,†}, Mark T. Swihart¹

1. Department of Chemical and Biological Engineering, University at Buffalo, The State University of New York, Buffalo, NY, 14260, USA
2. William G. Lowrie Department of Chemical and Biomolecular Engineering, The Ohio State University, 315 Koffolt Laboratories, 151 West Woodruff Avenue, Columbus, OH, 43210, USA
3. Department of Chemical and Biomolecular Engineering, ETSIIT, University of Cantabria, Avda. Los Castros s/n, 39005 Santander, Spain
4. Department of Electrical Engineering, University at Buffalo, The State University of New York, Buffalo, NY, 14260, USA

† Deceased

Table of contents

Fig. S1 Five arbitrary planes at the T-outlet

Fig. S2 MATLAB calculation of the distribution of z -component of magnetic field for five arbitrary planes a) at $z = 0.55$ mm away from the magnet; b) at $z = 0.65$ mm; c) at $z = 1$ mm; d) at $z = 1.35$ mm; e) at $z = 1.45$ mm; and f) $B_{z,max}$ with respect to distance from the magnet

Fig. S3 Changes of volume and diameter of 10% (v/v) ferrofluid for 25 μm depth a) volume b) diameter

Fig. S4 Changes of volume and diameter of 50% (v/v) ferrofluid for 25 μm depth a) volume b) diameter

Fig. S5 Changes of volume and diameter of 10% (v/v) ferrofluid for 30 μm depth a) volume b) diameter

Fig. S6 Changes of volume and diameter of 50% (v/v) ferrofluid for 30 μm depth a) volume b) diameter

Fig. S7 Changes of volume and diameter of 10% (v/v) ferrofluid for 40 μm depth a) volume b) diameter

Fig. S8. Changes of volume and diameter of 50% (v/v) ferrofluid for 40 μm depth a) volume b) diameter

Fig. S9 Droplet diameter after pinch off vs. capillary number (Ca) analysis. a) Ca changes for three channel depths; b-d) droplet diameter vs. Ca for channel depths of b) 25 μm ; c) 30 μm ; and d) Ca of 40 μm depth for 50% (v/v) under an applied magnetic field




Fig. S1 Five arbitrary planes at the T-outlet




Fig. S2 MATLAB calculation of the distribution of z-component of magnetic field for five arbitrary planes a) at $z = 0.55 \text{ mm}$ away from the magnet; b) at $z = 0.65 \text{ mm}$; c) at $z = 1 \text{ mm}$; d) at $z = 1.35 \text{ mm}$; e) at $z = 1.45 \text{ mm}$; and f) $B_{z,\max}$ with respect to distance




Fig. S3 Changes of volume and diameter of 10% (v/v) ferrofluid for 25 μm depth a) volume b) diameter




Fig. S4 Changes of volume and diameter of 50% (v/v) ferrofluid for 25 μm depth a) volume b) diameter




Fig. S5 Changes of volume and diameter of 10% (v/v) ferrofluid for 30 μm depth a) volume b) diameter




Fig. S6 Changes of volume and diameter of 50% (v/v) ferrofluid for 30 μm depth a) volume b) diameter




Fig. S7 Changes of volume and diameter of 10% (v/v) ferrofluid for 40 μm depth a) volume b) diameter




Fig. S8 Changes of volume and diameter of 50% (v/v) ferrofluid for 40 μm depth a) volume b) diameter




Fig. S9 Droplet diameter after pinch off vs. capillary number (\mathcal{Ca}) analysis. a) \mathcal{Ca} changes for three channel depths; b-d) droplet diameter vs. \mathcal{Ca} for channel depths of b) 25 μm ; c) 30 μm ; and d) 40 μm depth for 50% (v/v) under an applied magnetic field