

Electronic Supporting Information

Piezoelectric Ba and Ti co-doped BiFeO₃ textured films: selective growth of solid solutions or nanocomposites

Quentin Micard,^a Anna L. Pellegrino^a Raffaella Lo Nigro,^b Ausrine Bartasyte,^c Guglielmo G. Condorelli,^{a,*} and Graziella Malandrino^{a,*}

^aDipartimento di Scienze Chimiche, Universita' Catania, and INSTM UdR Catania, Viale A. Doria 6, I-95125 Catania, Italy

^bIstituto per la Microelettronica e Microsistemi, IMM-CNR, Strada VIII n 5, 95121 Catania, Italy

^c FEMTO-ST Institute, University of Bourgogne Franche-Comté CNRS UMR 6174, 26 Rue de l'Epitaphe, F-25030 Besançon, France.




Fig. S1 Raw XRD patterns with indicated the peak positions of potential phases. For the films and peak position phase see the legend in the figure.





Fig. S2 EDX spectra of the A-type and B-type films.





Fig. S3 C 1s XPS spectral region of a) A-type and b) B-type samples.




Fig. S4 Deconvolution of the Bi 4f7/2 XPS spectral region of a) A-type and b) B-type samples.




Fig. S5 XRD patterns in the 42-48° range of the B-type sample (—) compared with undoped BiFeO₃ (—), and singly doped Bi_(1-x)Ba_xFeO₃ (—) films grown on SrTiO₃:Nb (100) substrates.