## Electronic supplementary Information

## Anchoring zinc-doped carbon dots on paper-based chip for

## highly sensitive fluorescent detection of copper ions

Qinglan Miao,‡<sup>a</sup> Ji Qi,‡<sup>b</sup> Yuanyuan Li,<sup>a</sup> Xinxia Fan,<sup>a</sup> Dongmei Deng, \*<sup>a</sup> Xiaoxia Yan,<sup>a</sup> Haibo He <sup>a</sup> and Liqiang Luo \*<sup>a</sup>

a. College of Sciences, Shanghai University, Shanghai 200444, PR China. E-mail: dmdeng@shu.edu.cn (D. Deng); luck@shu.edu.cn (L. Luo)

b. CAS Key Laboratory of Coastal Environmental Processes and Ecological Remediation, Shandong Provincial Key Laboratory of Coastal Environmental Processes, Research Centre for Coastal Environmental Engineering and Technology, Yantai Institute of Coastal Zone Research, Chinese Academy of Sciences, Yantai 264003, China

‡ These authors contributed equally

## **Contents:**

Fig. S1 (A) Top view of basic component of the wheel type paper-based microfluidic chip. (B)The operation of microfluidic chip. (C) The assembling wheel type paper-based microfluidic chip.(D) Photograph of the chip under UV light (365 nm).

**Fig. S2** (A) Fluorescence spectra of Zn-CDs at different concentrations. (B) Fluorescence spectra of Zn-CDs (160 times) at different excitation wavelength.

Fig. S3 (A) The high-resolution C 1s spectrum of Zn-CDs. (B)The high-resolution O 1s spectrum of Zn-CDs.

Fig. S4 FT-IR spectra of (A) L-Cys and (B) MNA.

Fig. S5 SEM images of (A) bare paper and (B) MNA-L-Cys-paper@Zn-CDs.

**Fig. S6** Fluorescence microscopy images of (A) bare paper, (B) paper@Zn-CDs and (C) MNA-L-Cys-paper@Zn-CDs. Scale bars are 50 μm.

**Fig. S7** Fluorescence spectra of the MNA-L-Cys-paper@Zn-CDs at (A) different grafting time of Zn-CDs and (B) different concentrations of Zn-CDs.

Fig. S8 Fluorescence spectra of Zn-CDs at different mass ratio of the precursors (citric acid:zinc acetate).

Fig. S9 Fluorescence intensity of different sensing sites.



Fig. S1 (A) Top view of basic component of the wheel type paper-based microfluidic chip. (B)The operation of microfluidic chip. (C) The assembling wheel type paper-based microfluidic chip.(D) Photograph of the chip under UV light (365 nm).



Fig. S2 (A) Fluorescence spectra of Zn-CDs at different concentrations. (B) Fluorescence spectra

of Zn-CDs (160 times) at different excitation wavelength.



Fig. S3 (A) The high-resolution C 1s spectrum of Zn-CDs. (B)The high-resolution O 1s spectrum of Zn-CDs.



Fig. S4 FT-IR spectra of (A) L-Cys and (B) MNA.



Fig. S5 SEM images of (A) bare paper and (B) MNA-L-Cys-paper@Zn-CDs.



Fig. S6 Fluorescence microscopy images of (A) bare paper, (B) paper@Zn-CDs and (C) MNA-L-

Cys-paper@Zn-CDs. Scale bars are 50  $\mu m.$ 



Fig. S7 Fluorescence spectra of the MNA-L-Cys-paper@Zn-CDs at (A) different grafting time of

Zn-CDs and (B) different concentrations of Zn-CDs.



Fig. S8 Fluorescence spectra of Zn-CDs at different mass ratio of the precursors (citric acid:zinc

acetate).



Fig. S9 Fluorescence intensity of different sensing sites.