## Supporting Information

## Cubic-like Co/NC Composites Derived From ZIF-67 with Dual Control Strategy of Size and Graphitization Degree for Microwave Absorption

Jiaqi Tao<sup>1,2</sup>, Linling Xu<sup>1,2</sup>, Wan Li<sup>3</sup>, Jinsen Hou<sup>3</sup>, Pengshu Yi<sup>1,2</sup>, Ping Chen<sup>4</sup>, Jintang Zhou<sup>1,2,\*</sup>, Zhengjun Yao<sup>1,2,\*</sup>

<sup>1</sup> College of Materials Science and Technology, Nanjing University of Aeronautics and Astronautics, Nanjing, 211100, Jiangsu, People's Republic of China

<sup>2</sup> Key Laboratory of Material Preparation and Protection for Harsh Environment (Nanjing University of Aeronautics and Astronautics), Ministry of Industry and Information Technology, Nanjing, 211100, Jiangsu, People's Republic of China

<sup>3</sup> Shanghai Composites Science & Technology Co.,Ltd, Shanghai 201112, People's Republic of China

<sup>4</sup> School of Electronic Science and Engineering, Nanjing University, Nanjing, 210023 Jiangsu, People's Republic of China

\* Corresponding author. College of Materials Science and Technology, Nanjing University of Aeronautics and Astronautics, Nanjing, 211100, Jiangsu, People's Republic of China.

**Phone:** +8613814115821

E-mail address: imzjt@126.com (J, Zhou), yaozj1921@126.com (Z. Yao).

## Contents

Figure S1. O1s Spectrum of 20-600, 30-600 and 40-600.

Figure S2. Schematic diagram of the effect of different particle sizes on the conductive path.

Figure S3. Cole-Cole curves of 30-500, 30-700 and 30-800.

Figure S4. The electromagnetic parameters of 30-600 at (a) 25 wt% and (b) 35 wt%.



Figure S1. O1s Spectrum of 20-600, 30-600 and 40-600.



Figure S2. Schematic diagram of the effect of different particle sizes on the conductive path.



Figure S3. Cole-Cole curves of 30-500, 30-700 and 30-800.



Figure S4. The electromagnetic parameters of 30-600 at (a) 25 wt% and (b) 35 wt%.