

Supporting Information

Application of super-stretched self-healing elastomer based on methyl vinyl silicone rubber for wearable electronic sensors

Tianwen Yu,^a Yifei Shan,^a Zhixi Li,^a Xiaoxiao Wang,^a Huanan Cui,^c Kun Yang,^{*b} Yongyan Cui,^{*a}

^a.College of Chemical Engineering and Materials Science, Tianjin University of Science and Technology, Tianjin 300457, PR China

^b.Institute of Molecular Aggregation Science, Tianjin University, Tianjin 300072, PR China

^c.China Academy of Space Technology, Beijing 100094, PR China

* Co-corresponding-authors: yangkun1463@126.com (K. Yang), cyy@tust.edu.cn (Y. Cui).




Figure S1 ¹H NMR spectrum of MVSR elastomer.




Figure S2 ¹H NMR spectrum of MVSR-ICA elastomer.




Figure S3 ¹H NMR spectrum of MVSR-UPY elastomer.




Figure S4 GPC curves of MVSR, MVSR-ICA and MVSR-UPY.




Figure S5 DSC curve of MVSR-UPY with different molar ratios.




Figure S6 TGA curves of MVSR-UPY with different molar ratios.




Figure S7 Stress-strain curves of MVSR-UPY₃ at different tensile rates.




Figure S8 Frequency sweeping of storage (G') and loss (G'') moduli of the elastomer (a) MVSR-UPY₁ (b) MVSR-UPY₂ (c) MVSR-UPY₃ (d) MVSR-UPY₄.




Figure S9. Recovery and reprocessing performance of MVSR-UPY elastomers. (a) The reprocessing of elastomers, (b) Stress-strain curves of MVSR-UPY elastomers with different processing times at a tensile rate of 100 mm min^{-1} .




Figure S10 Schematic diagram of sensor structure




Figure S11 Schematic diagram of sensor recovery and reorganization.