

Supplementary data

One-step fabrication of stretchable and anti-oil-fouling nanofiber membrane for solar steam generation

Mantang He^a, Huijie Liu^a, Liming Wang^{a,*}, Xiaohong Qin^{a,*}, Jianyong Yu^b

^a *Key Laboratory of Textile Science & Technology, Ministry of Education, College of Textiles, Donghua University, Shanghai 201620, China*

^b *Innovation Center for Textile Science and Technology, Donghua University, Shanghai 201620, China*

* Corresponding authors.

E-mail addresses: wangliming@dhu.edu.cn (L. Wang), xhqin@dhu.edu.cn (X. Qin)




Fig. S1. Wicking measurements of PDA@CNT/PU nanofiber membrane in oil layer on water and oil-in-water emulsion.




Fig. S2. Digital photograph of fabricated device for solar steam generation test.




Fig. S3. IR images of PU nanofiber membrane on water, and PDA@CNT/PU nanofiber membrane on water, water with oil layer and oil-in-water emulsion before 1 sun illumination.




Fig. S4. Light absorption spectrum of PDA@CNT/PU nanofiber membrane.




Fig. S5. Evaporation rate of PDA@CNT/PU nanofiber membrane under cycle numbers of test.




Fig. S6. Resistance of PDA@CNT/PU nanofiber membrane under different strain.




Fig. S7. Resistance of PDA@CNT/PU nanofiber membrane after different uniaxial stretching cycle under strain of 100%.