

Supplementary information

Passivation of Triple Cation perovskites using Guanidinium Iodide in inverted solar cells for improved open-circuit voltage and stability

Aditya S. Yerramilli¹, Yuanqing Chen^{1,2}, Terry Alford^{1,3*}

¹School for Matter, Transportation and Energy, Arizona State University, AZ, 85282, United States

²Department of Materials Physics and Chemistry, Xi'an University of Technology, Xi'an, 710048, China

³Materials Science Program, African University of Science and Technology, Abuja FCT, Nigeria

***Corresponding author: Prof. Alford (TA@asu.edu)**




Fig. S1. XRD spectra of perovskite with different GUAI loading conditions prepared on ITO/glass (* represents PbI_2)




Fig. S2. SEM images of perovskite with different GUAI loading conditions prepared on an ITO/glass substrate




Fig. S3. Box plot of J_{sc} for perovskite control with different GUAI loading conditions




Fig. S4. Box plot of V_{OC} for perovskite control with different GUA loading conditions




Fig. S5. Box plot of FF for perovskite control with different GUA loading conditions




Fig. S6. J_{SC} decay of perovskite control device with different GUAI loading conditions




Fig. S7. V_{OC} decay of perovskite control device with different GUAI loading conditions




Fig. S8. FF decay of perovskite control device with different GUAI loading conditions