## **Supplementary Information**

## Enhanced electrochemical performances based on ZnSnO3 microcubes functionalized in-

## doped carbon nanofibers as free-standing anode materials

Xiaoqiang Li<sup>a,b</sup>, Guangguang Guan<sup>c,d</sup>, Chuanjin Yu<sup>b</sup>, Bingjie Cheng<sup>b</sup>, Xin Chen<sup>a</sup>, Kaiyin Zhang<sup>e</sup>, Jun Xiang<sup>a,\*</sup>

<sup>a</sup> School of Science, Jiangsu University of Science and Technology, Zhenjiang 212100, China

<sup>b</sup> Institute of Materials Science and Engineering, Beijing University of Technology, Beijing 100124, China

° Shenyang National Laboratory for Materials Science, Institute of Metal Research, Chinese Academy of Sciences,

Shenyang 110016, China

<sup>d</sup> School of Materials Science and Engineering, University of Science and Technology of China, Shenyang 110016,

China

<sup>e</sup> College of mechanical and electrical engineering, Wuyi University, Wuyishan 354300, China

\*Corresponding author.

*E-mail address:* jxiang@just.edu.cn (J. Xiang).



Fig. S1. TG curves of ZSO@CNFM-1, ZSO@CNFM-2 and ZSO@CNFM-3.



Fig. S2. High-resolution N 1s spectra of ZSO@CNFM-2.



Fig. S3. SEM image of CNFM.



Fig. S4. HRTEM image of ZSO@CNFM-2



Fig. S5. (a) Nitrogen adsorption-desorption isotherms and (b) pore-size distributions of ZSO@CNFM-1, ZSO@CNFM-2 and ZSO@CNFM-3.



Fig. S6. (a) Nyquist plot and (b) corresponding  $Z_{re}$  vs.  $\omega^{-1/2}$  plot in the low-frequency range for the CNFM electrode.



Fig. S7. SEM image of ZSO@CNFM-2 after 100 cycles at 100 mA  $g^{-1}.$