

Supplementary Material for on-line publication only

Electroactive nanofibrous dressing with temperature monitoring for wound healing

Liguo Yang^{a1}, Chenglin Li^{b1}, Xiangyan Zhang^{c*}, Yongxin Li^{c*}, Shangpeng Liu^a, Jiwei Li^{*a, d}

^a College of Textiles and Clothing, Industrial Research Institute of Nonwovens and Technical Textiles, Qingdao University, Qingdao, 266071, China.

^b Department of Biochemistry and Microbiology, Qingdao University Medical College, Qingdao University, Qingdao, 266003, China.

^c Department of Pathology, Department of Vascular Surgery, The Affiliated Hospital of Qingdao University, Qingdao University, Qingdao, 266003, China.

^d Shandong Center for Engineered Nonwovens, Qingdao, 266071, China.

¹ These authors contributed equally

Corresponding Author* Emails: jiweili@qdu.edu.cn (Jiwei Li); feige5552006@126.com (Xiangyan Zhang); li.yongxin@outlook.com (Yongxin Li);




Figure S1. Metal coating area percentage of different samples.




Figure S2. The measured voltage of Ag/Zn@PLA at different time.




Figure S3. The monitored temperature change of Ag/Zn@PLA treated wound at different time.




Figure S4. The monitored temperature change of skin wounds by an infrared imager.