

Electronic Supplementary Information (ESI)

Improvement of Rate Capability of All-Solid-State Cells with Fe-Based Polysulfide Positive Electrode Materials by Modifying Microstructure

Tomonari Takeuchi,^{a} Noboru Taguchi,^a Mitsunori Kitta,^a Toyonari Yaji,^b*

Misae Otoyama,^a Kentaro Kuratani,^a and Hikari Sakaebe^{a,c}

^a National Institute of Advanced Industrial Science and Technology (AIST)

Midorigaoka 1-8-31, Ikeda, Osaka 563-8577, Japan

^b Synchrotron Radiation Center, Ritsumeikan University

Kusatsu, Shiga 525-8577, Japan

^c Present address: Kyushu University, 6-1 Kasuga koen, Kasuga-shi, Fukuoka 816-8580,

Japan

XANES spectra

Figure S1 shows the S K-edge X-ray absorption near-edge structure (XANES) spectra for the $\text{Li}_8\text{FeS}_5\text{-Li}_2\text{FeS}_2$ and $\text{Li}_8\text{FeS}_5\text{-H}$ samples.




Figure S1 S K-edge XANES spectra for the $\text{Li}_8\text{FeS}_5\text{-H}$ and $\text{Li}_8\text{FeS}_5\text{-Li}_2\text{FeS}_2$ samples. Li_2S , S, and FeS were used as references.