

Supporting Information

Pr₂Ni_{0.8}Co_{0.2}O_{4+δ} impregnated La_{0.6}Sr_{0.4}CoO_{3-δ} oxygen electrode for efficient CO₂ electroreduction in solid oxide electrolysis cells

**Binbin Liu,^a Zeming Li,^{cd} Guoping Xiao,^{cd} Xian-Long Du,^{*cd} Huichao Yao,^b
Ruoyun Dai,^b Xiulin Wang,^{*b} Jian-Qiang Wang^{cd} and Tao Li^{*a}**

^a Engineering Research Center of Large-Scale Reactor Engineering and Technology, Ministry of Education, State Key Laboratory of Chemical Engineering, East China University of Science and Technology, Shanghai 200237, China

^b CNOOC Gas and Power Group Co., Ltd, Beijing, 100020, China

^c Key Laboratory of Interfacial Physics and Technology, Shanghai Institute of Applied Physics, Chinese Academy of Sciences, Shanghai 201800, China. E-mail: duxianlong@sinap.ac.cn

^d University of Chinese Academy of Sciences, Beijing 100049, China

* Corresponding Author

E-mail: duxianlong@sinap.ac.cn




Fig S1. XRD patterns of LSC, PNCO and PNCO⁶-LSC.




Fig S2. Long-term stability of LSC oxygen electrode cells.