

Supplementary information

Concurrent improvements of coercivity and corrosion resistance for Nd₆Fe₁₃Ga reconstructed Nd-Fe-B sintered magnets

Rui Shen¹, Shuainan Xu¹, Congyi Wang², Enxiang Yang³, Xiaolian Liu^{1, 3,*}, Song
Fu^{1,2}, Weiyang Jin³, Yu Pan¹, Lizhong Zhao¹, Pengfei Guan⁴, Xuefeng Zhang^{1,*}

1. Institute of Advanced Magnetic Materials, College of Materials and
Environmental Engineering, Hangzhou Dianzi University, Hangzhou, 310018,
China

2. Zhejiang Innuovo Magnetism Co., Ltd., Jinhua 322118, China

3. Ningbo Permanent Magnets Co., Ltd., Ningbo 315032, China

4. Beijing Computational Science Research Center, Beijing 100193, China

5.




Fig. S1. DSC curves of Nd-Fe-Ga alloy.




Fig. S2. Corrosion morphology evolution of different phases for the investigated magnets with different Nd-Fe-Ga addition after immersing in 3.5% NaCl solution varying for different times. *In-situ* images in the local area for 0 (a), 1% (b), 2% (c) and 4% addition(d) ranging from 0 to 90 min.