Supplementary Information (SI) for Journal of Materials Chemistry C. This journal is © The Royal Society of Chemistry 2025

Supplementary Information

Enhanced energy storage performances under low electric fields in(1x)Na_{0.5}Bi_{0.5}TiO₃-xSr_{0.7}Bi_{0.2}(Al_{0.5}Ta_{0.5})O₃ relaxor ferroelectric ceramics: Impact of Sr_{0.7}Bi_{0.2}(Al_{0.5}Ta_{0.5})O₃ on structure and electrical properties

Jiangnan Hu,^a Xiangping Jiang,*^a Chao Chen,^a Na Tu,^a Xin Nie,^a Chong Zhao,^a

Dandan Wei,^a Canxu Zheng,^a Jialin Gu,^a Qian Yuan,^a and Xiaokun Huang^{*a}

^aJiangxi Key Laboratory of Advanced Ceramic Materials, Department of Materials Science and Engineering, Jingdezhen Ceramic University, Jingdezhen, 333403, Jiangxi, China

*Corresponding author: Email (Xiangping Jiang) jiangxp64@163.com Email (Xiaokun Huang) hxk 16@126.com



Fig. S1. Sum of the Gaussian peaks contributing to the XRD patterns within the 2θ ranges of 39.5°-40.5° and 46.0°-47.0° for (1-*x*)NBT-*x*SBAT.



Fig. S2. Grain size distributions of (1-*x*)NBT-*x*SBAT.