

Supplementary Information N°1 for

Harmonizing the assessment of (Green) Hydrogen Supply Chain: a modular and parametrized Life Cycle Assessment Framework.

Gabriel Magnaval ^{1,2,*}, Maël Mouhoub ², Anne-Marie Boulay¹, Manuele Margni²

¹ CIRAIG, Department of Chemical Engineering, Polytechnique Montreal, 2500 Chem. De Polytechnique, Montreal, Canada

² HES-SO Valais-Wallis, Rue de l'Industrie 21, Sion, Switzerland

* corresponding author details: gabriel.magnaval@polymtl.ca

Aim of this document

This document is a supplementary material dedicated to the critical analysis of the literature performed in the paper (section 2). It provides more details for each research gap identified, by explaining the problem and its consequence, and by indicating the literature sources illustrating the problem.

In the following section, a structured analysis of ten FC&EL LCA reviews [1–10], complemented by two additional methodological contributions [11,12] and thirty-three practical use cases [13–47] has been conducted (see **Supplementary Information S11b** which compiles in a table the main elements of analysis for the 34 use cases). This analysis follows a three-step structure: (1) identification of the sources of methodological divergence that currently hinder the development of a consistent LCA framework; (2) examination of practitioners requirements from the LCA framework depending on their intended goals; (3) Comparison of these needs with the observed methodological gaps, and identification of potential solutions that will be explored in this paper to address the challenges and advancing the harmonization of LCA for FC&EL systems. The methodology and the results of this critical review are represented in Figure 1.

1. Sources of LCA methodological inconsistencies

This section outlined the sources of lack of harmonization identified in the critical review of existing LCAs on FC & EL technologies. These issues were grouped into two categories, following the ISO framework for LCA: research gaps related to the definition of the scope and to the modeling of the life cycle inventory.

1.1 Divergence in the scope of FC&EL LCA

According to ISO standards, defining the scope of an LCA involves establishing the functional unit—which quantifies the primary function of the system and serves as the basis for comparison—and identifying all processes necessary to fulfill this function. The scope must therefore align with both the technologies under study and their prospective functions. A key finding from the review is the lack of harmonization in scope definition across LCA studies, stemming from three main issues.

A diversity of functional units for the FC&EL LCA studies has been identified in the literature [4,6,7,10]. These functional units can be categorized into two groups: (a) those representing an intermediate product within the hydrogen supply chain, and (b) those capturing the final service delivered by the assessed technology. The first group includes units linked to system components—such as “kW of installed capacity” [17,35,41] or “m² of stack area” [20] - as well as units representing hydrogen production without specifying its application or the requirements to fulfill a downstream function. Hydrogen production is typically expressed with either mass-based (“1 kg of H₂ produced” [2,5,6,14,18,43]) or energy-based (“1 MJ or 1 kWh of H₂ produced” [13,16,44]) functional units. In contrast, the second group includes functional units that reflect the end-use of hydrogen, aligning more closely with its role in delivering a final service. For chemical applications, the functional unit has been set as “1 kg of hydrogen supplied at a specified pressure, temperature, and purity” [11,15,19,24,34,45–47], highlighting that hydrogen produced, prepared and distributed to the consumer. Other examples include “1 vehicle-kilometer driven” or “1 ton-kilometer driven” for transportation applications [4,8,26,28,29], “1 MJ or 1 kWh of energy supplied” [7,12,25,27,32,36], or “1 kWh of electricity stored” [31,33] for energy carrier applications.

As studies become inherently difficult to compare when functional units differ, efforts toward harmonization are essential. While functional units must be tailored to the specific function of each hydrogen application, consistency within a given application—regardless of the technology assessed or the intended LCA goal—can be targeted. However, the coexistence of the two categories of functional units identified above (intermediate product-based vs. service-based) reveals that such harmonization is lacking, as studies assessing the same application may select a functional unit from either category.

Two main issues emerge regarding system boundaries. First, since system boundaries should reflect the functional unit and the context of the study, the diversity of functional units naturally

leads to variability in which processes are included. Hydrogen supply chain processes such as compression, purification, storage, and distribution should be included when end-use functional units are defined but fall outside the system boundaries when intermediate product-based functional units are used [4, 14, 16, 18, 43, 44]. Second, beyond these expected variations, the review highlights inconsistencies between the functional units defined and the system boundaries actually applied. In several cases, the supply chain processes (storage, distribution) are excluded without justification, even when they are necessary to fulfill the stated end-use function [4, 6–9, 36, 39]. In addition, core components of the FC & EL systems are frequently omitted. This includes the balance-of-plant (BoP) (i.e. auxiliary equipment) essential for system operation [4, 14, 35, 37, 41], end-of-life treatment of the stack [4, 14, 24, 37, 42, 43], or in rare cases, the stack itself [34]. Finally, at the stack level, core layers are sometimes excluded from the boundaries, such as the end-plates [13, 37, 39] or the current collectors [13, 20, 35, 37, 42]. These omissions compromise the representativeness and completeness of the assessments.

1.2 Divergence in the Life Cycle Inventory

According to ISO, the life cycle inventory (LCI) aims to quantify the flows which links the elementary processes in the system boundaries. This step requires describing how the elementary processes are linked, collecting data on all relevant inputs, and transparently reporting data sources, data quality, and underlying assumptions. Two main limitations of the LCI have been identified in this review: (1) incomplete or inconsistent reporting, and (2) discrepancies in the relationships between the elementary processes.

The review identifies several levels of problems in inventory reporting. The most critical issue is the complete lack of reporting for parts or entire inventories in some studies, which severely undermines transparency [17, 21, 28, 29, 40]. While most papers do report inventory data, they systematically present static datasets—that is, fixed, computed, or aggregated values without dynamic relationships between parameters. This limits the adaptability of the studies and complicates efforts to update or refine them. In addition, units of measurement vary across inventories. For example, stack manufacturing data may be reported per kW of stack, per m² of stack, or per unit of stack. However, the parameters required to convert between these units are often not provided, making it difficult to reconcile datasets and ultimately limiting comparability.

A second limitation lies in the inconsistent definition of key performance parameters—particularly system efficiency and system size. A variety of efficiency conventions exist: stack-limited or system efficiencies [24, 42, 48]; LHV-based [12, 24, 46, 49], HHV-based [5, 50] or thermoneutral-based efficiencies [51, 52]; beginning of life or average efficiencies [15, 45, 53]. Similarly, the system capacity can be defined and compared in terms of electrical power [13, 18, 46] or hydrogen flowrate [19, 20, 42]. This diversity leads to misunderstandings and reveals a lack of clarity regarding what exactly is being assessed and how key parameters are interrelated. This underscores the need for more explicit definition of efficiency or capacity depending on the context.

The third limitation of the inventory lies in its dependency on specific technology capacity and technology readiness levels (TRLs). Comparison between systems is only relevant when the TRL and the capacity of the system are equivalent [10]. Yet, as FC&EL are still emerging technologies, their maturity and size are varying from one technology family to another [13]. To improve comparability across studies, there is a need for robust up-sizing (i.e., estimating the impacts of larger system configurations) and up-scaling (i.e., modeling future improvements in environmental performance) methodologies. As for now, up-sizing of FC & EL systems for LCA draws on economic empirical correlations [18, 26], but these rely on cost-based relationships that are not necessarily representative of environmental dynamics, as economies of scale do not directly translate to environmental benefits. Up-scaling is commonly

addressed by building prospective datasets based on expert judgment or field targets [10,14,42,43,45]. However, the lack of transparent reporting in many studies makes it difficult to distinguish between empirical and prospective datasets [10], ultimately leading to the creation of inconsistent inventories that combine empirical stack data with prospective operational performances [13,16,20,24].

2 – Methodological requirements derived from intended objectives of the LCA

In addition to addressing these challenges, a unified framework must also meet the specific requirements of each intended goal to ensure its applicability across all contexts. According to ISO, the intended goal of an LCA defines the purpose of the study. As outlined in the introduction, the main goals of LCAs applied to fuel cells and electrolyzers (FC&EL) include: (i) comparing FC&EL technologies with conventional or alternative systems providing equivalent functions, (ii) benchmarking different FC&EL families, and (iii) supporting the eco-design of FC&EL systems. The following section details the methodological requirements derived from each intended objectives.

First, comparing FC&EL technologies with alternative systems providing equivalent functions requires a consistent system scope across technologies to ensure a proper supply chain-to-supply chain comparison. For this reason, functional units that reflect the final service delivered by hydrogen are required for this intended goal.

Second, comparing different families of FC&EL technologies requires consistent LCA modeling. This means that the system boundaries should be identical across all FC&EL families, including supply chain, system components and stack functional layers. A common inventory modeling with aligned assumptions for data collection and preparation is also required.

Third, for eco-design purposes, high-detailed inventories are essential. They provide greater precision and transparency, and they support sensitivity and contribution analyses needed to identify system hotspots and design levers. However, for other intended goals, highly detailed datasets are often avoided, as aggregated inventories are less time-consuming to compile and offer useful simplifications that enhance usability—particularly for broader-scale assessments and non-expert audiences. These divergent interests explain the variability in the level of detail observed across the literature. Stack manufacturing may rely on a generic model taken from LCA databases such as ecoinvent [18,25,26,29,33], static inventories at the stack level [14,19,22,24,46], layer level [13,27,35–37,39,43] or parametrized inventories [15,16,20,42]. Similarly, the BoP equipment is modeled with varying granularity—from aggregated material quantities [24,39,43,46] to detailed representations [15,18,27,36]. The key challenge lies in establishing granular LCI modeling for FC&EL systems that can accommodate different levels of detail, enabling inventories designed for eco-design to be meaningfully aggregated and compared with those developed for other purposes.

- [1] Chavez DL, Azzaro-Pantel C, Montignac F, Ruby A. Integrating life cycle assessment in multi-objective optimization of green hydrogen systems: a review of literature and methodological challenges. *Renewable and Sustainable Energy Reviews* 2025;217:115689. <https://doi.org/10.1016/j.rser.2025.115689>.
- [2] Ajeeb W, Costa Neto R, Baptista P. Life cycle assessment of green hydrogen production through electrolysis: A literature review. *Sustainable Energy Technologies and Assessments* 2024;69:103923. <https://doi.org/10.1016/j.seta.2024.103923>.
- [3] Shaya N, Glöser-Chahoud S. A Review of Life Cycle Assessment (LCA) Studies for Hydrogen Production Technologies through Water Electrolysis: Recent Advances. *Energies (Basel)* 2024;17:3968. <https://doi.org/10.3390/en17163968>.
- [4] Valente A, Iribarren D, Dufour J. Life cycle assessment of hydrogen energy systems: a review of methodological choices. *Int J Life Cycle Assess* 2017;22:346–63. <https://doi.org/10.1007/s11367-016-1156-z>.
- [5] Bhandari R, Trudewind CA, Zapp P. Life cycle assessment of hydrogen production via electrolysis – a review. *J Clean Prod* 2014;85:151–63. <https://doi.org/10.1016/j.jclepro.2013.07.048>.
- [6] Sola A, Rosa R, Ferrari AM. Green Hydrogen and Its Supply Chain. A Critical Assessment of the Environmental Impacts. *Adv Sustain Syst* 2025;9. <https://doi.org/10.1002/adsu.202400708>.
- [7] Rinawati DI, Keeley AR, Takeda S, Managi S. Life-cycle assessment of hydrogen utilization in power generation: A systematic review of technological and methodological choices. *Frontiers in Sustainability* 2022;3. <https://doi.org/10.3389/frsus.2022.920876>.
- [8] Rinawati DI, Keeley AR, Takeda S, Managi S. A systematic review of life cycle assessment of hydrogen for road transport use. *Progress in Energy* 2022;4:012001. <https://doi.org/10.1088/2516-1083/ac34e9>.
- [9] Ishimoto Y, Wulf C, Schonhoff A, Kuckshinrichs W. Life cycle costing approaches of fuel cell and hydrogen systems: A literature review. *Int J Hydrogen Energy* 2024;54:361–74. <https://doi.org/10.1016/j.ijhydene.2023.04.035>.
- [10] Martinez GE, Degens R, Espadas-Aldana G, Costa D, Cardellini G. Prospective Life Cycle Assessment of Hydrogen: A Systematic Review of Methodological Choices. *Energies (Basel)* 2024;17:4297. <https://doi.org/10.3390/en17174297>.
- [11] Fuel Cells and Hydrogen 2 Joint Undertaking. *Hydrogen roadmap Europe – A sustainable pathway for the European energy transition*. Publications Office; 2016. <https://doi.org/doi/10.2843/341510>.
- [12] Bargiacchi E, Puig-Samper G, Iribarren D, Dufour J. D2.2 Definition of FCH-LCA Guidelines. 2022.
- [13] Wei X, Sharma S, Waeber A, Wen D, Sampathkumar SN, Margni M, et al. Comparative life cycle analysis of electrolyzer technologies for hydrogen production: Manufacturing and operations. *Joule* 2024;8:3347–72. <https://doi.org/10.1016/j.joule.2024.09.007>.
- [14] Delpierre M, Quist J, Mertens J, Prieur-Vernat A, Cucurachi S. Assessing the environmental impacts of wind-based hydrogen production in the Netherlands using ex-ante LCA and scenarios analysis. *J Clean Prod* 2021;299:126866. <https://doi.org/10.1016/j.jclepro.2021.126866>.
- [15] Magnaval G, Debonnet T, Margni M. *Integrated LCA and Eco-design Process for Hydrogen Technologies: Case Study of the Solid Oxide Electrolyser*. 2025. <https://doi.org/LAPSE:2025.0030v2>.
- [16] Riemer M, Duval-Dachary S, Bachmann TM. Environmental implications of reducing the platinum group metal loading in fuel cells and electrolyzers: Anion exchange membrane versus proton exchange membrane cells. *Sustainable Energy*

- Technologies and Assessments 2023;56:103086.
<https://doi.org/10.1016/j.seta.2023.103086>.
- [17] Sarner S, Schreiber A, Menzler NH, Guillon O. Recycling Strategies for Solid Oxide Cells. *Adv Energy Mater* 2022;12. <https://doi.org/10.1002/aenm.202201805>.
- [18] Gerloff N. Comparative Life-Cycle-Assessment analysis of three major water electrolysis technologies while applying various energy scenarios for a greener hydrogen production. *J Energy Storage* 2021;43. <https://doi.org/10.1016/j.est.2021.102759>.
- [19] Terlouw T, Bauer C, McKenna R, Mazzotti M. Large-scale hydrogen production via water electrolysis: a techno-economic and environmental assessment. *Energy Environ Sci* 2022;15:3583–602. <https://doi.org/10.1039/D2EE01023B>.
- [20] Zhao G, Kraglund MR, Frandsen HL, Wulff AC, Jensen SH, Chen M, et al. Life cycle assessment of H₂O electrolysis technologies. *Int J Hydrogen Energy* 2020;45:23765–81. <https://doi.org/10.1016/j.ijhydene.2020.05.282>.
- [21] Shen H, Crespo del Granado P, Jorge RS, Löffler K. Environmental and climate impacts of a large-scale deployment of green hydrogen in Europe. *Energy and Climate Change* 2024;5:100133. <https://doi.org/10.1016/j.egycc.2024.100133>.
- [22] Hermesmann M, Müller TE. Green, Turquoise, Blue, or Grey? Environmentally friendly Hydrogen Production in Transforming Energy Systems. *Prog Energy Combust Sci* 2022;90:100996. <https://doi.org/10.1016/j.pecs.2022.100996>.
- [23] Patel GH, Havukainen J, Horttanainen M, Soukka R, Tuomaala M. Climate change performance of hydrogen production based on life cycle assessment. *Green Chemistry* 2024;26:992–1006. <https://doi.org/10.1039/D3GC02410E>.
- [24] Bareiß K, de la Rua C, Möckl M, Hamacher T. Life cycle assessment of hydrogen from proton exchange membrane water electrolysis in future energy systems. *Appl Energy* 2019;237:862–72. <https://doi.org/10.1016/j.apenergy.2019.01.001>.
- [25] Gandiglio M, Marocco P, Bianco I, Lovera D, Blengini GA, Santarelli M. Life cycle assessment of a renewable energy system with hydrogen-battery storage for a remote off-grid community. *Int J Hydrogen Energy* 2022;47:32822–34. <https://doi.org/10.1016/j.ijhydene.2022.07.199>.
- [26] Zhang X, Bauer C, Mutel CL, Volkart K. Life Cycle Assessment of Power-to-Gas: Approaches, system variations and their environmental implications. *Appl Energy* 2017;190:326–38. <https://doi.org/10.1016/j.apenergy.2016.12.098>.
- [27] Di Florio G, Macchi EG, Mongibello L, Baratto MC, Basosi R, Busi E, et al. Comparative life cycle assessment of two different SOFC-based cogeneration systems with thermal energy storage integrated into a single-family house nanogrid. *Appl Energy* 2021;285. <https://doi.org/10.1016/j.apenergy.2020.116378>.
- [28] Ahmadi P, Khoshnevisan A. Dynamic simulation and lifecycle assessment of hydrogen fuel cell electric vehicles considering various hydrogen production methods. *Int J Hydrogen Energy* 2022;47:26758–69. <https://doi.org/10.1016/j.ijhydene.2022.06.215>.
- [29] Desantes JM, Molina S, Novella R, Lopez-Juarez M. Comparative global warming impact and NO_x emissions of conventional and hydrogen automotive propulsion systems. *Energy Convers Manag* 2020;221:113137. <https://doi.org/10.1016/j.enconman.2020.113137>.
- [30] Fernández-Dacosta C, Shen L, Schakel W, Ramirez A, Kramer GJ. Potential and challenges of low-carbon energy options: Comparative assessment of alternative fuels for the transport sector. *Appl Energy* 2019;236:590–606. <https://doi.org/10.1016/j.apenergy.2018.11.055>.
- [31] Mostert C, Ostrander B, Bringezu S, Kneiske TM. Comparing Electrical Energy Storage Technologies Regarding Their Material and Carbon Footprint. *Energies (Basel)* 2018;11:3386. <https://doi.org/10.3390/en11123386>.
- [32] Bionaz D, Marocco P, Ferrero D, Sundseth K, Santarelli M. Life cycle environmental analysis of a hydrogen-based energy storage system for remote applications. *Energy Reports* 2022;8:5080–92. <https://doi.org/10.1016/j.egypr.2022.03.181>.

- [33] Yamaki A, Fujii S, Kanematsu Y, Kikuchi Y. Comparative Life Cycle Assessment of Energy Storage Systems for Connecting Large-Scale Wind Energy to the Grid. *Journal of Chemical Engineering of Japan* 2024;57. <https://doi.org/10.1080/00219592.2024.2406316>.
- [34] Hren R, Vujanović A, Van Fan Y, Klemeš JJ, Krajnc D, Čuček L. Hydrogen production, storage and transport for renewable energy and chemicals: An environmental footprint assessment. *Renewable and Sustainable Energy Reviews* 2023;173:113113. <https://doi.org/10.1016/j.rser.2022.113113>.
- [35] Häfele S, Hauck M, Dailly J. Life cycle assessment of the manufacture and operation of solid oxide electrolyser components and stacks. *Int J Hydrogen Energy* 2016;41:13786–96. <https://doi.org/10.1016/j.ijhydene.2016.05.069>.
- [36] Longo S, Cellura M, Guarino F, Brunaccini G, Ferraro M. Life cycle energy and environmental impacts of a solid oxide fuel cell micro-CHP system for residential application. *Science of The Total Environment* 2019;685:59–73. <https://doi.org/10.1016/j.scitotenv.2019.05.368>.
- [37] Spreafico C. Prospective life cycle assessment to support eco-design of solid oxide fuel cells. *International Journal of Sustainable Engineering* 2024;17:379–96. <https://doi.org/10.1080/19397038.2024.2355899>.
- [38] Velandia Vargas JE, Seabra JEA. Fuel-cell technologies for private vehicles in Brazil: Environmental mirage or prospective romance? A comparative life cycle assessment of PEMFC and SOFC light-duty vehicles. *Science of The Total Environment* 2021;798:149265. <https://doi.org/10.1016/j.scitotenv.2021.149265>.
- [39] Staffell I, Ingram A. Life cycle assessment of an alkaline fuel cell CHP system. *Int J Hydrogen Energy* 2010;35:2491–505. <https://doi.org/10.1016/j.ijhydene.2009.12.135>.
- [40] Hydrogen Council. Hydrogen decarbonization pathways: A life-cycle assessment. 2021.
- [41] Campos-Carriedo F, Pérez-López P, Dufour J, Iribarren D. A parametric life cycle framework to promote sustainable-by-design product development: Application to a hydrogen production technology. *J Clean Prod* 2024;469:143129. <https://doi.org/10.1016/j.jclepro.2024.143129>.
- [42] Schropp E, Campos-Carriedo F, Iribarren D, Naumann G, Bernäcker C, Gaderer M, et al. Environmental and material criticality assessment of hydrogen production via anion exchange membrane electrolysis. *Appl Energy* 2024;356:122247. <https://doi.org/10.1016/j.apenergy.2023.122247>.
- [43] Krishnan S, Corona B, Kramer GJ, Junginger M, Koning V. Prospective LCA of alkaline and PEM electrolyser systems. *Int J Hydrogen Energy* 2024;55:26–41. <https://doi.org/10.1016/j.ijhydene.2023.10.192>.
- [44] Moranti A, Riva F, Bachmann TM, Dailly J. Environmental performance of a metal-supported protonic ceramic cell and an electrolyte-supported solid oxide cell for steam electrolysis. *Int J Hydrogen Energy* 2024;92:1284–97. <https://doi.org/10.1016/j.ijhydene.2024.10.221>.
- [45] Gerhardt-Mörsdorf J, Peterssen F, Burfeind P, Benecke M, Bensmann B, Hanke-Rauschenbach R, et al. Life Cycle Assessment of a 5 MW Polymer Exchange Membrane Water Electrolysis Plant. *Advanced Energy and Sustainability Research* 2024;5. <https://doi.org/10.1002/aesr.202300135>.
- [46] Battelle. Fuel Cell Systems for Primary Power and Combined Heat and Power Applications. 2017.
- [47] Nami H, Rizvandi OB, Chatzichristodoulou C, Hendriksen PV, Frandsen HL. Techno-economic analysis of current and emerging electrolysis technologies for green hydrogen production. *Energy Convers Manag* 2022;269:116162. <https://doi.org/10.1016/j.enconman.2022.116162>.
- [48] Kim H, Choe C, Lee A, Lim H. Application of green hydrogen with theoretical and empirical approaches of alkaline water electrolysis: Life cycle-based techno economic and environmental assessments of renewable urea synthesis. *Int J Hydrogen Energy* 2023;48:16148–58. <https://doi.org/10.1016/j.ijhydene.2023.01.062>.

- [49] Ali D, Gazey R, Aklil D. Developing a thermally compensated electrolyser model coupled with pressurised hydrogen storage for modelling the energy efficiency of hydrogen energy storage systems and identifying their operation performance issues. *Renewable and Sustainable Energy Reviews* 2016;66:27–37. <https://doi.org/10.1016/j.rser.2016.07.067>.
- [50] Peharz G, Dimroth F, Wittstadt U. Solar hydrogen production by water splitting with a conversion efficiency of 18%. *Int J Hydrogen Energy* 2007;32:3248–52. <https://doi.org/10.1016/j.ijhydene.2007.04.036>.
- [51] Acevedo Y, Prosser J, Huya-Kouadio J, McNamara K, James B. Hydrogen Production Cost with Alkaline Electrolysis. 2023. <https://doi.org/10.2172/2203367>.