

## **Optimization of diffusion dynamics in Mn-doped Co<sub>3</sub>O<sub>4</sub>/rGO hybrid electrodes for efficient energy storage in asymmetric supercapacitors**

Farhan Ahmad<sup>1</sup>, Abdul Shakoor<sup>1</sup>, Ahsan Iqbal<sup>1</sup>, Asif Mahmood<sup>2</sup>, Waheed Al-Masry<sup>2</sup>,  
Farooq Ahmad<sup>1</sup>, Shahid Atiq<sup>1,\*</sup>

<sup>1</sup>*Centre of Excellence in Solid State Physics, University of the Punjab, Lahore-54590, Pakistan*

<sup>2</sup>*College of Engineering, Chemical Engineering Department, King Saud University, 11421, Riyadh, Saudi Arabia*




Fig. S1 (a) XRD patterns of CoO, MDCoO-I, MDCoO-II, MDCoO-III, and MDCoO-IV, and (b) XRD patterns of rGO and nickel foam.




Fig. S2 CV curves at 5 mV/s for all samples.




Fig. S3(a-e) Contribution parameters  $k_1$  and  $k_2$  (average slope and intercept of anodic and cathodic peak) from linear fitting using

$$\text{equation } \frac{i_{peak}}{v^{0.5}} = k_1 v^{0.5} + k_2 \text{ for all samples.}$$




Fig. S4 (a) CV curves of CoO at different scan rates and (b-f) Capacitive and diffusive contributions for CoO content at different scan rates.





Fig. S5 (a) CV curves of MDCoO-I at different scan rates and (b-f) Capacitive and diffusive contributions for MDCoO-I at different scan rates.



**Fig. S6 (a)** CV curves of MDCoO-II at different scan rates and **(b-f)** Capacitive and diffusive contributions for MDCoO-II at different scan rates.





Fig. S7 (a) CV curves of MDCoO-III at different scan rates and (b-f) Capacitive and diffusive contributions for MDCoO-III at different scan rates.



**Fig. S8 (a)** CV curves of MDCoO-IV with different scan rates and **(b-f)** Capacitive and diffusive contributions for MDCoO-IV content at different scan rates.