Supporting information

Effects of borax loading on self-healing properties of epoxidized natural rubber

Tamonwan Chantaramanee ^a, Supachok Tanpichai ^{*bc} Anyaporn Boonmahitthisud ^{*ade}

^aDepartment of Materials Science, Faculty of Science, Chulalongkorn University, Bangkok, 10330, Thailand.

^bLearning Institute, King Mongkut's University of Technology Thonburi (KMUTT), 126, Pracha Uthit road, Bangmod, Thung Khru, Bangkok, 10140, Thailand.

°Cellulose and Bio-based Nanomaterials Research Group, King Mongkut's University of

Technology Thonburi (KMUTT), 126, Pracha Uthit road, Bangmod, Thung Khru, Bangkok,

10140, Thailand.

^dCenter of Excellence in Green Materials for Industrial Application, Faculty of Science,

Chulalongkorn University, Bangkok, 10330, Thailand.

eCenter of Excellence on Petrochemical and Materials Technology, Chulalongkorn University,

Bangkok, 10330, Thailand.

* Email: anyaporn.b@chula.ac.th, supachok.tan@kmutt.ac.th



Figure S1. Cross-sectional surfaces of (a) 10B and (b) 30B materials.



Figure S2. Fracture surface of the (a) 0B (b) 10B materials after tensile deformation.