

Irreversible Phase Transitions in BiFeO₃-SrTiO₃ Lead-Free Piezoceramics

Songhao Fu^a, Muhammad Wasim^b, Hareem Zubairi^c, Xiaojiao Liu^d, Annette K Kleppe^d, Xinzhen Wang^e, Antonio Feteira^b, Ge Wang^{c*}, Zhilun Lu^{a*}

^aSchool of Chemical and Process Engineering, University of Leeds, Leeds, LS2 9JT, UK

^bSchool of Engineering and Built Environment, Sheffield Hallam University, Sheffield, S1 1WB UK

^cDepartment of Materials, University of Manchester, Manchester, M13 9PL, UK

^dDiamond Light Source Ltd, Harwell Science and Innovation Campus, Didcot, OX11 0DE, UK

^eSchool of Materials Science and Engineering, Shandong University of Science and Technology, Qingdao, 266590, China

*Correspondence authors: z.lu@leeds.ac.uk; ge.wang@manchester.ac.uk

Table S1. Summary of XRD Rietveld refinement results for (1-x)BF-xST ceramics (x = 0.42, 0.44, 0.46, and 0.48) ceramics.

Compositions	Lattice Parameter <i>a</i> (Å)	Cell Volume (Å ³)	GOF
x = 0.42	3.94588(5)	61.43723(2)	1.39
x = 0.44	3.94456(4)	61.37559(2)	1.35
x = 0.46	3.94357(4)	61.32939(18)	1.29
x = 0.48	3.94287(4)	61.29674(18)	1.26




Fig. S1. 3D and contour maps of (a) {200}_{pc} (b) {220}_{pc} and {222}_{pc} XRD profiles at ψ=90° of x = 0.44 ceramic during *in-situ* poling synchrotron XRD.