

Supplementary Information

Synergistic Interface and Entropy Engineering in Ferrite/Nitrides Heterogeneous High-Entropy Composites for Broadband Microwave Absorption

*Zhiyue He[‡], Han Liu[‡], Zhenyu Xu, Tianhong Xu, Naixin Zhai, Zhenzhi Cheng, Fei Gao,
Guangsheng Luo, and Weiping Zhou**

*School of Physics and Materials Science, Nanchang University, Nanchang 330031, People's
Republic of China*

[‡] These authors contributed equally to the work

* Authors to whom correspondence should be addressed: wpzhou@ncu.edu.cn.




Figure S1. XRD patterns of as-prepared HEOs




Figure S2. (a) SEM images of sample N-MnZn (b-i) EDS images of sample N-MnZn.




Figure S3. 2D projection diagram of (a) N-MnZn, (b) N-MnMg, (c) N-ZnMg




Figure S4. Calculated 3D contour maps, 2D plots, and RL curves of (a),(d),(g) N-MnCr, (b),(e),(h) N-ZnCr, (c),(f),(i) N-MgCr.




Figure S5. (a-f) RL curves and (g-l) electromagnetic parameters of the six un-nitrided high-entropy ferrites.




Figure S6. (a) conductive loss of the six samples; (b) polarization loss of the six samples.




Figure S7. Plot of reflection loss (RL) versus optimal matching thickness (t_m) for (i) N-MnZn and (h) N-MnMg.