




Supplementary material for Evaluating the Sustainability of Electrochemical CO₂ Capture Technology through LCA and LCC: A Winery Industry Application

Prince Sungdewie Adama Nopuo, Javiera Francisca Gutiérrez-Espinoza, Carmen M. Fernández-Marchante, Pedro M. Izquierdo-Cañas, Esteban García, Manuel A. Rodrigo Rodrigo, Justo Lobato*

An emerging alternative to amine scrubbing is the use of electrochemically produced sodium hydroxide to fix CO₂ as carbonate. The mechanism of this process is based on the fact that in a wet alkaline medium, CO₂ is physically absorbed and instantly reacts with NaOH according to the reaction pathways presented in equations 1-3 [7].



In a highly alkaline medium (excess NaOH), reaction 3 is carried out immediately after reaction 2, resulting in the formation of sodium carbonate as the product. However, for prolonged capture, NaOH becomes limiting, and the reverse of reaction 3 sets in, producing sodium bicarbonate as the product.

The EDEN technology is designed to operate in both electrolysis and fuel-cell modes. The electrolysis reactions involve anodic oxidation of water to oxygen (Equation (4)) and oxidation of chloride ions to chlorine gas (Equation (5)). Chlorine may undergo chemical disproportionation to hypochlorous acid (Equation (7)) after dissolving in water (Equation (6)), which can then dissociate into hypochlorite ions (Equation (6)). The cathode reduces water to hydrogen and hydroxide ions (Equation (9)). Also, chlorine generated at the anode can be reduced at the cathode due to crossover, potentially competing with water reduction and producing chloride ions [9].









Table S1: Material selection for each scenario studied.

FU = 1 g CO ₂ Captured			Unit	Material Quantity	Material Quantity per FU	Scenarios				
Module	Component	Material Selected in SimaPro				1	2	3	4	5
Materials (Manufacturing + Processing)										
Electrolyzer	Cathode	Titanium, {GLO} market for titanium Cut-off, U	g	6.159	3.33E-04	✓	✓	✓	✓	X
	Anode electrode, Cell C	Titanium, {GLO} market for titanium Cut-off, U	g	1.547	8.35E-05	✓	X	✓	X	X
		Carbon black, {GLO} market for carbon black Cut-off, U	g	0.042	2.27E-06					
		Rhodium, {GLO} market for rhodium Cut-off, U, for Ruthenium catalyst	g	0.007	3.82E-07					
		Platinum, {GLO} market for platinum Cut-off, U, for Platinum (catalyst)	g	0.006	3.38E-07					
		Tetrafluoroethylene, {GLO} market for tetrafluoroethylene Cut-off, U	g	0.003	1.73E-07					
	Anode electrode, Cell B	Titanium, {GLO} market for titanium Cut-off, U, for Titanium Sheet	g	10.613	5.73E-04	X	✓	X	✓	X
Rhodium, {GLO} market for rhodium Cut-off, U, for Ruthenium catalyst		g	0.064	3.46E-06						
Platinum, {GLO} market for platinum Cut-off, U, for Platinum (catalyst)		g	0.043	2.30E-06						
Titanium, {GLO} market for titanium Cut-off, U, for Titanium (catalyst)		g	0.427	2.30E-05						
Membrane (Nafion)	Tetrafluoroethylene, {GLO} market for tetrafluoroethylene Cut-off, U	g	1.676	9.05E-05	✓	✓	✓	✓	X	
	Sulfuric acid, {RER} market for sulfuric acid Cut-off, U	g	0.419	2.26E-05						
Gasket	Silicone product, {RER} market for silicone product Cut-off, U	g	38.426	2.08E-03	✓	✓	✓	✓	X	
Screws support	Steel, stainless 304, {RNA} quarto plate	g	91.176	4.92E-03	✓	✓	✓	✓	X	
Screws	Polyethylene terephthalate, {GLO} market for polyethylene terephthalate, granulate, bottle grade Cut-off, U	g	25.176	1.36E-03	✓	✓	✓	✓	X	
End and Bipolar	Methyl methacrylate, {RER} market for methyl methacrylate Cut-off, U	g	143.210	7.73E-03	✓	✓	✓	✓	✓	

	Plates	Methyl methacrylate, {RER} market for methyl methacrylate Cut-off, U	g	48.251	2.61E-03					
Storage and Connections	Pipes	Silicone product, {RER} market for silicone product Cut-off, U	g	91.1	4.92E-03	✓	✓	✓	✓	(x1)
	Tanks (2)	Methyl methacrylate, {RER} market for methyl methacrylate Cut-off, U	g	469.389	5.07E-03					✓
		Methyl methacrylate, {RER} market for methyl methacrylate Cut-off, U	g	158.150	1.71E-03					
Compressor	Screws	Steel, stainless 304, {RNA} quarto plate	g	32.123	5.01E-05	✓	✓	✓	✓	✓
	Pipes	Silicone product, {RER} market for silicone product Cut-off, U	g	14.231	3.14E-05					
	Casing	Polycarbonate, granulate, {GLO} market for Cut-off, U	g	69.721	1.23E-04					
	Electronics	Electronics, for control units, {GLO} market for Cut-off, U	g	215.121	3.63E-04					
Pump(x2)	Screws	Steel, {RNA} stainless 304, quarto plate	g	29.888	4.91E-05	✓	✓	✓	✓	(x1)
	Pipes	Silicone product, {RER} market for silicone product Cut-off, U	g	17.682	2.91E-05					✓
	Casing	Polycarbonate, granulate, {GLO} market for Cut-off, U	g	68.052	1.12E-04					
	Electronics	Electronics, for control units, {GLO} market for Cut-off, U	g	208.358	3.43E-04					
DC power supply	DC power supply	Steel, chromium steel 18/8 {GLO} market for Cut-off, U	g	332.270	5.46E-04	✓	✓	✓	✓	✓
		Cable, unspecified {GLO} market for Cut-off, U	g	92.593	1.52E-04					
		Polyethylene, high-density, granular {GLO} market for Cut-off, U	g	934.053	1.54E-03					
		Electronics, for control units, {GLO} market for Cut-off, U	g	41.884	6.89E-05					
Absorption Column	Plastic body	Polyethylene terephthalate, {GLO} market for polyethylene terephthalate, granulate, bottle grade Cut-off, U	g	618.48	3.67E-03	X	X	✓	✓	✓
		Ethylene glycol, {RER} market for ethylene glycol Cut-off, U	g	68.72	4.08E-04					
	Sphere glass	Glass tube, borosilicate, {GLO} market for glass tube, borosilicate Cut-off, U	g	2000	1.19E-02					
	Screws	Steel, {RNA} stainless 304, quarto plate	g	467.5	2.78E-03					
	Gasket	Silicone product, market for silicone product Cut-off, U	g	34.7	2.06E-04					
Operation										
Feedstock	Electrolyte	Sodium chloride, brine solution, {GLO} market for sodium chloride, brine solution Cut-off, U	g		24.57	✓	✓	✓	✓	X
	Solvent	Neutralising agent, sodium hydroxide-equivalent, {RER} sodium hydroxide to the generic market for neutralising agent Cut-off, U	g		2.27	X	X	X	X	✓
Energy Source	Electricity	Photovoltaic module, building-integrated, for slanted-roof installation {RER} photovoltaic module production, building-integrated, for slanted-roof installation Cut-off, U	kWh		4.74E-03	✓	✓	X	X	X
					7.81E-03	X	X	✓	✓	X
					2.32E-04	X	X	X	X	✓

Table S2: Electricity prices, emission factors, and emissions prices considered (sourced from Ecoinvent database).

Electricity source	Price,	Emission factor	Emissions price
--------------------	--------	-----------------	-----------------

	€/kWh	(kg CO ₂ /kWh)	(€/t CO ₂ -eq)
Italy grid mix	0.195	0.35	65
Chile grid mix	0.11	0.51	4.6
Spain grid mix	0.17	0.21	65
France grid mix	0.171	0.09	65
California grid mix	0.065	0.38	40
Spain's solar energy	0.05	0.07	65
Spain wind energy	0.04	0.01	65
Spain's nuclear energy	0.1	0.01	65
Off-grid solar (Spain)	0.0073	0.006	65




Figure S1. Time course formation of HClO in the catholyte and anolyte




Figure S2. Time course of electrolytes pH trend: (A) anolyte and (B) catholyte for short duration, (C) Catholyte and (D) anolyte for longer duration.




Figure S3. Time course of carbonate formation during electro-absorption of CO₂ at 15 mL/min: (A) Comparison of different tested conditions and (B) 120 minutes of CO₂ absorption considering conditions of B2.




Figure S4: Optimization of studied variables, (A) influence of NaOH flow rate and CO₂ flow rate on the capture efficiency in column absorption, (B) influence of NaOH concentration on the capture efficiency in column absorption, (C) influence of CO₂ flow rate on the capture efficiency in electro-absorption.




Figure S5. Daily profiles of mass and probable alcohol content of the fermentation broth.

Table S3: Composition of fermentation broth (wine sample) before and after fermentation.

Sampling Description	pH	°Brix	Total Acidity (g/L)	Malic Acid (g/L)	Lactic Acid (g/L)	Acetic Acid (g/L)	Citric Acid (g/L)	Tartaric Acid (g/L)	Succinic Acid (g/L)	Glycerol (g/L)	Glucose + Fructose (g/L)	Alcohol (% v/v)
Initial sample (unfermented must)	3.10	16.64	5.60	1.91	–	–	3.39	1.79	–	–	154.00	0.30

Sampling Description	pH	°Brix	Total Acidity (g/L)	Malic Acid (g/L)	Lactic Acid (g/L)	Acetic Acid (g/L)	Citric Acid (g/L)	Tartaric Acid (g/L)	Succinic Acid (g/L)	Glycerol (g/L)	Glucose + Fructose (g/L)	Alcohol (% v/v)
Final sample after fermentation	3.09	–	7.40	1.66	0.16	–	3.52	1.97	0.66	5.09	0.18	8.40




Figure S6. Recipe Midpoint results for the studied CO₂ capture scenarios.