

## Supplementary Information (SI)

### Interface-Engineered HMS/PANI Thermoelectric Device for 3D Printer Waste Heat

#### Harvesting

Nishath Begum Jamal Mohammed<sup>a</sup>, Rajasekar Parasuraman<sup>a\*</sup>, Pandiyarasan Veluswamy<sup>c</sup>, Arunkumar Chandrasekhar<sup>b\*</sup>

- a. Department of Chemistry, School of Advanced Sciences, Vellore Institute of Technology (VIT), Vellore, Tamil Nadu 632 014, India*
- b. Nanosensors and Nanoenergy (NSNE) Lab, Department of Sensors and Biomedical Technology, School of Electronics Engineering, Vellore Institute of Technology, Vellore, Tamil Nadu, India*
- c. Smart and Innovative Laboratory for Energy Device Lab, Indian Institute of Information Technology, Design and Manufacturing, Kancheepuram, Tamil Nadu 600127, India*

Corresponding author mail ID: [arunkumar.c@vit.ac.in](mailto:arunkumar.c@vit.ac.in), [rajasekar.mgac@gmail.com](mailto:rajasekar.mgac@gmail.com)

## TGA analysis






Fig. S1. TGA analysis of HMS/PANI composites ranging from 0 to 80%.

## XPS analysis




**Fig. S2.** a) XPS analysis of PANI- I) Survey, II) C 1s, III) O 1s. b) XPS analysis of HMS/PANI (50%) - I) Survey, II) C 1s, III) O 1s, IV) Mn and V) Si.

## Hall coefficient measurement




**Fig. S3.** Hall coefficient measurement of the composite films - pure PANI, 10%, 50%, 80% of HMS content composites.

### Seebeck measurement setup



**Fig. S4.** Schematic representation of the home-built Seebeck coefficient measurement setup.

### Calculated dimensionless figure of merit ( $ZT$ )



**Fig. S5.** Calculated  $ZT$  of HMS/PANI composite thin films

### Real-time application




Fig. S6. Photo of the real-time application setup with the 3D printer in ideal condition.




Fig. S7. Photo of the real-time application setup of the thermoelectric device with the operational 3D printer.