

Design	Electrode center (μm)	Electrode width (μm)
Figure 4a	0.0	20.0
Figure 4b	0.0, 200.0, 400.0	20.0, 20.0, 20.0
Figure 4c	-130.5, -72.5, -17.5, 38.0, 90.5, 142.0, 192.5, 227.5	3.0, 5.0, 7.0, 8.0, 9.0, 10.0, 15.0, 41.0
Figure 4d	-427.0, -384.5, -339.5, -295.0, -252.5, -209.5, -167.5, -126.5, -86.0, -47.5, 0.0, 47.5, 86.0, 126.5, 167.5, 209.5, 252.5, 295, 339.5, 384.5, 427.0	20.0, 27.0, 25.0, 26.0, 27.0, 27.0, 27.0, 27.0, 28.0, 25.0, 40.0, 25.0, 28.0, 27.0, 27.0, 27.0, 27.0, 26.0, 25.0, 27.0, 20.0
Figure 4e	-358.0, -300.1, -245.0, -190.0, -137.1, -85.8, -35.2, 0.0, 35.2, 85.8, 137.1, 190.0, 245.0, 300.1, 358.0	3.0, 5.1, 6.9, 8.1, 9.2, 10.6, 13.4, 41, 13.4, 10.6, 9.2, 8.1, 6.9, 5.1, 3.0
Figure 4f	150.0	20.0
Figure 7c,f	0.0, 35.2, 85.8, 137.1, 190.0, 245.0, 300.1, 358.0	41.0, 13.4, 10.6, 9.2, 8.1, 6.9, 5.1, 3.0

Table 1 Coordinates of the electrode center and electrode width for all designs presented in this paper. The origin is taken to be at the center of the figures referenced.