

Electronic Supplementary Information

MnO₂ nanoflakes grown on 3D graphite network for enhanced electrocapacitive performance

Xiuxia Sun,^a Huanjing Wang,^a Zhibin Lei,^{a*} Zonghuai Liu,^a Lingling Wei ^{b*}

^a School of Materials Science and Engineering, Shaanxi Normal University, 620 West Chang'an Street, Xi'an, Shaanxi, 710119, China, Email: zblei@snnu.edu.cn; Tel: 86-29-81530810; Fax: 86-29-81530702

^b School of Chemistry and Chemical Engineering, Shaanxi Normal University, 620 West Chang'an Street, Xi'an, Shaanxi, 710119, China, Email: weill@snnu.edu.cn;

*Corresponding Authors:

Prof. Zhibin Lei, School of Materials Science and Engineering, Shaanxi Normal University, 199 South Chang'an Road, Xi'an, Shaanxi, 710062, China. Email: zblei@snnu.edu.cn; Tel: 86-29-81530810; Fax: 86-29-81530702

Dr. Lingling Wei, School of Chemistry and Chemical Engineering, Shaanxi Normal University, 620 West Chang'an Street, Xi'an, Shaanxi, 710119, China, Email: weill@snnu.edu.cn




Fig. S1 SEM image of 3D Ni foam.




Fig. S2. EDX spectrum of MnO₂-3DG-23% recorded in the selected area of Fig. 4d.




Fig. S3 The dependence of discharged current density at potential of 0.5 V (vs Ag/AgCl) on the scan rate for 3DG-MnO₂-13% electrode.




Fig. S4 The last 10 cycles of galvanostatic charge-discharge curves of 3DG-MnO₂-23% electrode at constant current density of 4.0 A/g in 1.0 mol/L Na₂SO₄ aqueous electrolyte.




Fig. S5 CV and galvanostatic charge-discharge profile of two-electrode capacitor constructed with 3DG-MnO₂-13% as the symmetric electrode.

