

Supporting Information

Segmented polymer nanowires and nanorods by one-step template wetting with hyperbranched polymer and linear polymer blend

Wei Tian,^{,a} Longbiao Huang,^b Duyang Zang,^a Chao Li,^a Jing Dang,^a and Dawei Wang^{*,c}*

^aThe Key Laboratory of Space Applied Physics and Chemistry, Ministry of Education and Shaanxi Key Laboratory of Macromolecular Science and Technology, School of Science, Northwestern Polytechnical University, Xi'an, 710072, P. R. China


^bDepartment of Industrial and Systems Engineering, The Hong Kong Polytechnic University, Hung Hom, Kowloon, Hong Kong, P. R. China

^cLehn Institute of Functional Materials, School of Chemistry and Chemical Engineering, Sun Yat-Sen University, Guangzhou 510275, P. R. China

*E-Mail: happytw_3000@nwpu.edu.cn or wdawei@mail.sysu.edu.cn

Scheme S1. Model polymers used in fabrication: (a) Ideal chemical structure of HBP-64-OH in Ref. S1;

(b) Synthetic routes of L-PMMA



REFERENCES

(S1) Xu J.; Luo S. Z.; Shi W. F.; Liu S. Y. *Langmuir*, **2006**, 22, 989-997.