-Supporting Information-

Extended Petroleum Hydrocarbon Bioremediation in Saline Soil Using Pt-free Multianodes Microbial Fuel Cells

Xiaojing Li, Xin Wang*, Yueyong Zhang, Lijuan Cheng, Jie Liu, Fan Li, Bingli Gao and Qixing Zhou*

MOE Key Laboratory of Pollution Processes and Environmental Criteria / Tianjin Key Laboratory of Environmental Remediation and Pollution Control / College of Environmental Science and Engineering, Nankai University, No. 94 Weijin Road, Nankai District, Tianjin 300071, China

*Corresponding Authors: Phone: (86)22-23507800; fax: (86)22-23501117; E-mail: zhouqx@nankai.edu.cn (Zhou Q.); xinwang1@nankai.edu.cn (Wang X.)

Items	Concentration (mg·kg ⁻¹)
рН	8.26
Conductivity (mS·cm ⁻¹)	1.994
Available nitrogen	46
Available phosphorus	198
Available potassium	525
Organic matter	142
Zn	54.4
Cu	9.1
Ni	14.2
Mn	58.4
Fe	3101.2
Pb	19.0
Cr	60.3
Cd	ND

Table S1 Properties of petroleum hydrocarbon contaminated soil.

ND: not detected under detection level of 0.1 $mg{\cdot}kg^{\text{-1}}$



Figure S1 pH (a) and conductivity (b) of soils sampled in different layers. Samples between two electrodes were sampled and marked as SL1, SL2, SL3, SL4 from the top to the bottom. NA: natural attenuation soil (the disconnected control).



Figure S2 Net degradation rates of TPHs at different layers in SMFC. The different lowercase indicates significant at the 0.01 level (2-tailed).